

PART NO. 59SCCMRxx
DESCRIPTION:

RG59/U CMR SC 20AWG 95% CB 1000' BLACK WOOD REEL

Rated Temperature(°C)	75°C
Product Rating	CCTV/UL/CMR
Flammability Test	CMR

APPLICATION

Digital, Analog, CATV, Satellite, Off-Air, Broad-band Communication

Reference Standard

NEC Article 800 and 820 Compliance

CONSTRUCTION


Conductor	Solid Bare Copper	
AWG	22awg	
Conductor Dia. (in.)	0.032in.	
Dielectric Material	Nitro Injected PE	
Outer Diameter (in.)	0.144in.	
Shields Number	2	
Coverage	1st	AP/APA
	2nd	95% Copper Braid
Jacket	Riser/PVC	
Nom. Outer Diameter(in.)	0.24in.	
Nominal Impedance	75 Ohm	

PERFORMANCE

Attenuation			Return Loss	
MHz	dB100ft	dB/100m	MHz	dB
1	0.20	0.65		
10	0.82	2.69	5-470	>20
100	2.62	8.59		
400	5.45	17.88	470-860	>20
700	7.52	24.67		
900	8.60	28.21	860-2500	>15

COLOR

Standard	Black
-----------------	--------------

STANDARD PACKAGING


Toll Free: (866) 945-5051
 Local: (770) 945-5051
 Fax: (770) 945-9582
www.commoditycables.com

