

CAT6A 23AWG/4PAIR 10G CMP SHIELDED F/UTP

PART NO. 6ASHDCMPRx

DESCRIPTION

- 23 AWG 4 Pair F/UTP 10G Category 6A cable tested to ANSI/TIA 568-C.2 for 10Gbps @500Mhz premium grade, high performance for top level network cabling for maximum headroom and bandwidth. Available in Wood Reel for easier installation.

FEATURES AND BENEFITS

- Category 6A performs at improved specifications, particularly in the area of alien cross-talk. Category 6A make use of their higher standards by allowing full 10GBASE-T transmission speeds of up to 10Gbps, at 500MHz of signal bandwidth, over 100 meters (330 ft)
- Improved cable temperature rating (90°C Plenum) for greater protection against increased operating temperatures and for high-wattage applications
- The internal separator optimizes each pair for superior electrical performance and maintains flexibility. This unique spline stabilizes each pair to create a smaller, round cable profile

APPLICATIONS

- IEEE 802.3 10G Base-T, 1000Base-T, 100Base-TX, 10Base-T, PoE, PoE+
- ANSI/TIA 854: 1000Base-TX
- CDDI, Token Ring, ATM
- Digital Video
- Broadband and Baseband Analog Video

STANDARD COMPLIANCES


- ANSI/TIA 568-C.2
- ANSI/TIA 862 (Building Automation)
- ISO/IEC 11801 Ed. 2.0 (Class EI)
- ICEA 8-102-700 (Category 6 or 5E)
- REACH Compliant
- CPR Compliant (Fully Comply to 305/2011 & EN 50575:2014-09)
- RoHS Compliant Directive 2002/95/EG

Toll Free: (866) 945-5051
Local: (770) 945-5051
Fax: (770) 945-9582
www.commoditycables.com




Drain Wire

Used to ease termination of the cable shield for crimping or soldering



PHYSICAL PROPERTIES

| | | |
|----------------------|-------------------------------|------------------------------|
| Conductor | Material | Bare copper |
| | Nominal Outside Diameter (mm) | 4x2x0.58 (±0.005) |
| Insulation | Material | FEP |
| | Diameter (± 0.05mm) | 1.15 |
| Screen Material | | AL-FOIL + Drain Wire (0.4TC) |
| Construction | | Shielded / Plenum |
| Jacket | Material | LS-FR PVC |
| | Average Thickness (mm) | 0.75 |
| | Minimum Point Thickness (mm) | 0.6 |
| | Outside Diameter (±0.2mm) | 7.8 |
| Rip Cord: | | Yes |
| Drain Wire: | | Yes |
| Packing | Length | 1000ft ± 4ft |
| | Weight | 49 lbs/Reel |
| Voltage Rating (Max) | | DC 300v |
| Test Flame Method | | CMP |



ELECTRICAL CHARACTERISTICS

| | | |
|--|------------------------|------------------|
| 1.0 - 250.0MHz characteristic impedance (ohms) | | 100Ω±15Ω |
| 250-650.0MHz Delay Skew (ns/100m) | | ≤45 |
| Pair-to-Ground Capacitance Unbalance (Pf/100m) | | ≤330 |
| Max. Conductor DC Resistance Unbalance (%) | | ≤5 |
| Max. Resistance Unbalance (%) | | 9.38/100m |
| Max Mutual Capacitance | | 5.6nF/100m |
| Max DC Loop Resistance | | 19.2Ω/100m |
| Min DC Insulation Resistance | | 150ms2/km |
| Max Propagation Delay Skew | | 40ns/100m |
| Before Aging | Tensile Strength (Mpa) | ≥10.0 |
| | Elongation (%) | ≥100 |
| After Aging | Tensile Strength (Mpa) | - |
| | Elongation (%) | ≥75 |
| Aging Period (°C x hrs) | | 100°C x 24h x 7d |
| Cold Bend (No Visible Crack) | | -20±2°C |
| Temperature Range | | -20°C ~ +75°C |
| Velocity of Propagation (%) NVP | | 70% |



1000' Wood Reel
Weight: 49 lbs.

AVAILABLE CATEGORY 6 (PART NUMBERS)

| PVC | Plenum | Shielded | Shielded Plenum | Direct Burial | Shielded Direct Burial |
|------------|------------|------------|-------------------|---------------|------------------------|
| 6ACMR234Rx | 6ACMP234Rx | 6ASHDCMRRx | 6ASHDCMPRx | 6AOUTG234RB | 6AOUTGSHDRB |

All values in this specification are nominal and are subjective to tolerances of +/- 10 to 15%. It is the sole responsibility of the user to have the most current specification. Specifications are subject to change without notice

CAT6A 23AWG/4PAIR 10G CMP SHIELDED F/UTP

PART NO. 6ASHDCMPRx

ELECTRICAL PERFORMANCE

ACRF - Attenuation to Crosstalk Ratio - Far End (dB/100m)

NEXT - Near End Crosstalk (dB/100m)

ACR - Attenuation to Crosstalk Ratio (dB/100m)

PSNEXT - Power Sum Near End Crosstalk (dB/100m)

ELFEXT - Equal Level Far End Crosstalk (dB/100m)

PSELFEXT - Power Sum Equal Level Far End Crosstalk (dB/100m)

RL - Return Loss (dB)

TCL - Transverse Conversion Loss (dB/100m)

ATT - Attenuation (dB/100m)

| FREQUENCY (MHz) | ATT (dB/100m) | RL (dB) | ACR (dB) | Next (dB) | PSNEXT (dB) | TCL (dB/100m) | PHASE DELAY | ELFEXT (dB/100m) | PSELFEXT dB/100m) |
|--------------------|------------------|------------|-------------|--------------|----------------|------------------|----------------|---------------------|----------------------|
| 1 | 2.1 | 20.0 | 72.2 | 75.3 | 72.3 | 40.0 | 570.0 | 68.0 | 65.0 |
| 4 | 3.8 | 23.0 | 61.5 | 66.3 | 63.3 | 40.0 | 552.0 | 56.0 | 53.0 |
| 8 | 5.3 | 24.5 | 55.4 | 61.8 | 58.8 | 40.0 | 546.7 | 49.9 | 46.9 |
| 10 | 5.9 | 25.0 | 53.4 | 60.3 | 57.3 | 40.0 | 545.4 | 48.0 | 45.0 |
| 16 | 7.5 | 25.0 | 48.8 | 57.2 | 54.2 | 38.0 | 543.0 | 43.9 | 40.9 |
| 20 | 8.4 | 25.0 | 46.4 | 55.8 | 52.8 | 37.0 | 542.1 | 42.0 | 39.0 |
| 25 | 9.4 | 24.3 | 43.7 | 54.3 | 51.3 | 36.0 | 541.2 | 40.0 | 37.0 |
| 31.25 | 10.5 | 23.6 | 41.4 | 52.9 | 49.9 | 35.1 | 540.4 | 38.1 | 35.1 |
| 62.5 | 15.0 | 21.5 | 32.4 | 48.4 | 45.4 | 32.0 | 538.6 | 32.1 | 29.1 |
| 100 | 19.1 | 20.1 | 25.2 | 45.3 | 42.3 | 30.0 | 537.6 | 28.0 | 25.0 |
| 200 | 27.6 | 18 | 12.2 | 40.8 | 37.8 | 27.0 | 536.5 | 22.0 | 19.0 |
| 250 | 31.1 | 17.3 | 7.2 | 39.3 | 36.3 | 26.0 | 536.3 | 20.0 | 17.0 |
| 300 | 34.3 | 16.8 | 2.9 | 38.3 | 35.5 | 25.2 | 535.5 | - | - |
| 400 | 40 | 15.9 | - | 37.8 | 35 | 24.0 | 535 | - | - |
| 500 | 45.3 | 15.2 | - | 36.5 | 34.3 | 23.0 | 533 | - | - |
| 600 | 50.1 | 14.5 | - | 35 | 33.5 | - | 532 | - | - |
| 650 | 52.4 | 13.9 | - | 34.6 | 31.2 | - | 530 | - | - |

Electrical performance with frequency over 500MHz is only for reference

| AVAILABLE JACKET COLORS | | |
|-------------------------|-----------------------|-------|
| STANDARD | BLUE | WHITE |
| SPECIAL | Per Customer Request* | |
| INSULATION COLORS | | |
| PAIR 1 | BLUE | WHITE |
| PAIR 2 | ORANGE | WHITE |
| PAIR 3 | GREEN | WHITE |
| PAIR 4 | BROWN | WHITE |

JACKETS ABBREVIATION

| | | |
|--------|----|--|
| Black | B | Last alphabetical character of each part number indicates the color code that the Jacket is available in. For example Part # 6CMR244Bx ("x" indicates all the colors to the left are available for this product. |
| White | W | |
| Gray | G | |
| Blue | O | |
| Yellow | Y | |
| Green | V | |
| Orange | OR | |
| Purple | P | |
| Red | R | |
| Pink | PI | |

Toll Free: (866) 945-5051
Local: (770) 945-5051
Fax: (770) 945-9582
www.commoditycables.com



*All values in this specification are nominal and are subject to tolerances of +/- 10 to 15%.
It is the sole responsibility of the user to have the most current specification. Specifications are subject to change without notice*