


**RG11 QUAD CMR COAXIAL CABLE 60% + 40% BRAID
COAXIAL**
PART NO. 11QCCSCMRRX
DESCRIPTION:

RG11 QUAD TYPE 60% + 40% BRAID
COAXIAL CABLE, BLACK JACKET, 1000FT
WOOD REEEL

Category: RG11 CMR

Test Standard: ETL


PERFORMANCE

Frequency (MHz)	ATT (dB)
55	0.96
211	1.90
300	2.25
400	2.60
550	3.05
750	3.65
870	4.00
1000	4.36
1350	4.98
1750	6.00
2150	6.70
2600	7.63
3000	8.24

STANDARD PACKAGE

Packing	Wooden Reel
Weight	62 lbs
Packing Length	1000 ft

Toll Free: (866) 945-5051
Local: (770) 945-5051
Fax: (770) 945-9582
www.commoditycables.com


CONSTRUCTION DETAILS

Conductor	Material	Solid copper clad steel		
	Nom. O.D. (mm)	1.63	up	+0.01
Insulation	Material	Foam PE		
	Diameter	7.11± 0.15 mm		
First Shield	Material	Aluminum/PET-Foil-Bonded		
Second Shield	Material	Aluminum Wire		
	Construction	0.15mm×16×6		
Third Shield	Material	Aluminum/PET/Aluminum-Foil		
Fourth Shield	Material	Aluminum Wire		
	Construction	0.15mmX16X4		
Sheath	Nom. Thickness	0.85mm		
	External O.D	10.00±0.20mm		
	Material	PVC (complies RoHS)		
	Color	BLACK		
Sheath Physical Properties	Before Aging Tensile Strength (Mpa)	≥13.8		
	Elongation(%)	≥180		
Electrical Characteristics (20°C)	Nom. Centre Conductor DC Resistance	13.0 ohm/kft		
	Velocity of Propagation (%)	85%		
	Nominal Capacitance	15.6 pF/ft		
	Impedance	75±3 Ohms		
	Jacket Spark Test Voltage	AC 3000V		
Temperature Range	-20°C to +70°C			