



www.commoditycables.com

PART NO. 1402UCMRRX

**Description**

14 AWG stranded bare copper 2 conductor riser

**Features and Benefits**

**RoHS Compliant**

Cables are manufactured to meet current NEC guidelines and are verified by outside standards organizations including c(UL)us and c(ETL)us. Footage marked descending.

**Suitable Application**

- Security Systems
- Sound/Audio System
- Intercom Systems
- Power-Limited Controls

**Standards**

NEC Articles: 725, 760, 800  
 22-16 AWG: CMR, CL2R, CL3R, FPLR  
 14-12 AWG: CL3R, FPLR

**Applicable Standards**

UL Type	CL2R, CL3R, FPLR
ROHS Compliant	Yes

**Electricals**

Voltage Rating	300 Volts
Conductors	ASTM B-3, B-8
Temperature Rating	-4°C to 75°C
Capacitance	22.5 pF/ft

**Print Legend**

COMMODITY CABLES, INC. 14 AWG 2C (UL)  
 TYPE CL2R, CL3R OR FPLR E498766 A1001.

Toll Free: (866) 945-5051  
 Local: (770) 945-5051  
 Fax: (770) 945-9582  
[www.commoditycables.com](http://www.commoditycables.com)

**Construction Details**

Total Number Conductors	2
AWG	14
Stranding	19 Strand
Conductor Material	Bare copper
Insulation Material	Polyvinylchloride
Insulation Thickness	.012"
Nominal Insulation Diameter	.098"
Color Code	Black/Red
Cabling Overall Lay	4" left hand lay
Final Jacket Material	Polyvinylchloride
Nominal Thickness	.015"
Jacket Color	White/Gray
Nominal Jacket Diameter	.225"
Ripcord	Yes

**Print (Surface Print)**

Inkjet	Yes
Sequential Foot Marks	Yes

**Preparation for Shipment**

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available. Shipping containers shall be constructed as to eliminate any possible damage to the cables due to shipment.



\*All values in this specification are nominal and are subjective to tolerances of +/- 10 to 15%. It is the sole responsibility of the user to have the most current specification. Specifications are subject to change without notice\*