



www.commoditycables.com

PART NO. 1602SCMRRG



Description

16 AWG 2 Conductor riser rated Grey jacket

Features and Benefits

RoHS Compliant

Cables are manufactured to meet current NEC guidelines and are verified by outside standards organizations including c(UL)us and c(ETL)us.

Footage marked descending.

Suitable Application

- Security Systems
- Sound/Audio System
- Intercom Systems
- Power-Limited Controls

Standards

NEC Articles: 25, 760, 800

22-16 AWG: CMR, CL2R, CL3R, FPLR

14-12 AWG: CL3R, FPLR

Applicable Standards

| | |
|----------------|------------------|
| UL Type | CL2R, CL3R, FPLR |
| ROHS Compliant | Yes |

Electricals

| | |
|--------------------|--------------|
| Operating Voltage | 300 V |
| Temperature Rating | -4°C to 75°C |
| Nom Capacitance | 34 pF/ft |

Print Legend

COMMODITY CABLES, INC. 16 AWG 2C (UL) TYPE CL3R/FPLR OR c(UL)us TYPE CMR E498766 A1001.

Made in USA

Toll Free: (866) 945-5051

Local: (770) 945-5051

Fax: (770) 945-9582

www.commoditycables.com

Construction Details

| | |
|-----------------------------|----------------------|
| Total Number Conductors | 2 |
| AWG | 16 |
| Stranding | 19 Strand |
| Conductor Material | Bare copper |
| Insulation Material | PVC |
| Insulation Thickness | .009" |
| Nominal Insulation Diameter | .074" |
| Color Code | Black/Red |
| Tape Material | Aluminium Mylar |
| Cabling Overall Lay | 3 1/2" left hand lay |
| Final Jacket Material | PVC |
| Nominal Thickness | .015" |
| Jacket Color | Gray |
| Nominal Jacket Diameter | .188" |
| Item Weight | 26 lb |
| Ripcord | Yes |

Print (Surface Print)

| | |
|-----------------------|-----|
| Inkjet | Yes |
| Sequential Foot Marks | Yes |

Preparation for Shipment

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available. Shipping containers shall be constructed as to eliminate any possible damage to the cables due to shipment.



All values in this specification are nominal and are subjective to tolerances of +/- 10 to 15%. It is the sole responsibility of the user to have the most current specification. Specifications are subject to change without notice