



www.commoditycables.com

PART NO. 1803UCMPRW



Description

18 AWG stranded bare copper 3 conductor Plenum

Features and Benefits

RoHS Compliant

Cables are manufactured to meet current NEC guidelines and are verified by outside standards organizations including c(UL)us and c(ETL)us.

Footage marked descending.

Suitable Application

- Security Systems
Sound/Audio System
Intercom Systems
Power-Limited Controls

Standards

- NEC Articles: 725, 760, 800
22-16 AWG: CMP, CL2P, CL3P, FPLP
14-12 AWG: CL3P, FPLP

Applicable Standards

Table with 2 columns: Standard Name (UL Type, ROHS Compliant) and Value (CMP, CL2P, CL3P, FPLP, Yes)

Electricals

Table with 2 columns: Property (Voltage Rating, Temperature Rating, Conductors, Capacitance) and Value (300 V, -4°C to 75°C, ASTM B-8, 20.5 pF/ft)

Print Legend

COMMODITY CABLES, INC. 18 AWG 3C (UL) TYPE CL3P/FPLP OR c(UL)us TYPE CMP E498766 A1001. Made in USA

Toll Free: (866) 945-5051

Local: (770) 945-5051

Fax: (770) 945-9582

www.commoditycables.com

Construction Details

Table with 2 columns: Property (Total Number Conductors, AWG, Stranding, Conductor Material, Insulation Material, Insulation Thickness, Nominal Insulation Diameter, Color Code, Cabling Overall Lay, Final Jacket Material, Nominal Thickness, Jacket Color, Nominal Jacket Diameter, Item Weight, Ripcord) and Value (3, 18, 7 Strand, Bare copper, Low smoke copolymer, .009", .064", Black, Red, White, 3" left hand lay, Low smoke copolymer, .015", White, .168", 30 lb, Yes)

Print (Surface Print)

Table with 2 columns: Property (Inkjet, Sequential Foot Marks) and Value (Yes, Yes)

Preparation for Shipment

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available. Shipping containers shall be constructed as to eliminate any possible damage to the cables due to shipment.



\*All values in this specification are nominal and are subjective to tolerances of +/- 10 to 15%. It is the sole responsibility of the user to have the most current specification. Specifications are subject to change without notice\*