

# PART NO. 2204SCMPBW



### www.commoditycables.com

# Description

22 AWG 4 conductor shielded with Plenum rated insulation and jacket

### Features and Benefits

**RoHS Compliant** 

Cables are manufactured to meet current NEC guidelines and are verified by outside standards organizations including c(UL)us and c(ETL)us. Footage marked descending.

## Suitable Application

Security Systems Sound/Audio System Intercom Systems **Power-Limited Controls** 

#### **Standards**

NEC Articles: 725, 760, 800 22-16 AWG: CMP, CL2P, CL3P, FPLP

14-12 AWG: CL3P, FPLP

### Applicable Standards

UL Type	CMP, CL3P, FPLP	
ROHS	Yes	
Compliant	100	

#### **Electricals**

Voltage Rating	300 Volts	
Temperature	-4°C to 75°C	
Rating	-4010130	
Capacitance	45.0 pF/ft	
CDR		

# **Print Legend**

COMMODITY CABLES, INC. 22 AWG 4C SHIELDED (UL) TYPE CL3P/FPLP OR c(UL)us TYPE CMP E498766 A1001. Made in USA

Toll Free: (866) 945-5051 Local: (770) 945-5051 Fax: (770) 945-9582 www.commoditycables.com







Construction Details	
Total Number Conductors	4
AWG	22
Stranding	7 Strand
Conductor Material	Bare copper
Insulation Material	Low smoke copolymer
Insulation Thickness	.007"
Nominal Insulation Diameter	.043"
Color Code	Black, Red, Green, White
Tape Material	Aluminium Mylar
Drain Wire Material	24 AWG tinned copper
Cabling Overall Lay	2 1/2" left hand lay
Final Jacket Material	Low smoke copolymer
Nominal Thickness	.015"
Jacket Color	White
Nominal Jacket Diameter	.138"
Ripcord	Yes

Print (Surface Print)	
Inkjet	Yes
Sequential Foot Marks	Yes

## Preparation for Shipment

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available. Shipping containers shall be constructed as to eliminate any possible damage to the cables due to shipment.