

**22/4C 7/STR UNSHIELDED CMR/CL2R GRAY
1000FT PULL BOX**
PART NO. 2204UCMRBG
DESCRIPTION:
**22/4C 7/STR UNSHIELDED CMR/CL2R GRAY
1000FT PULL BOX**

Meet RoHS ETL

Electrical Characteristics (20°C)	Capacitance	190pf/m
	DC Resistance (Ω/km) max	75
	Spark test	2.0kv
	Dielectric Test	1.5kv/min

Temperature Range	-20°C to + 75°C
-------------------	-----------------

STANDARD PACKAGING/JACKET COLOR


1000FT/PULL BOX

Weight: 15.9 lbs/BOX

Conductor	Material	Stranded Bare copper	
	Nom.O.D.(mm)	7/0.24	0.72mm
Insulation	Material	PVC	
	Diameter	1.1±0.05mm	
Sheath	Thickness	0.45±0.05mm	
	External O.D.	3.6+/-0.2mm	
	Surface	Wavy	
	Material	FR-PVC(complies RoHS)	
	Color	Gray	
Surface Printing	Letter height	2.5±0.3mm	
	Color	Black	
	Print error & Space	≤+0.5%, 1m	
Color	Black/Red/Green/White		
Packing Length	500ft+4ft		
Rip-cord	Yes	Drain wire	No
Sheath Physical Properties	Before Aging	Tensile Strength (Mpa)	≥ 10.0
		Elongation(%)	≥ 100
	Aging Period (°CXhrs) 100°CX24hX7d		
	After Aging Elongation(%)		≥ 75
Cold bend (-20±2°Cx4h)		8xCable O.D., No visible cracks	

Toll Free: (866) 945-5051
 Local: (770) 945-5051
 Fax: (770) 945-9582
www.commoditycables.com

