



www.commoditycables.com

# 14-2 UNSHIELDED PLENUM

PART NO. FPLP142URR

## Description

14 AWG Two Conductor Plenum

## Features and Benefits

### RoHS Compliant

Cables are manufactured to meet current NEC guidelines and are verified by outside standards organizations including c(UL)us and c(ETL)us. Footage marked descending.

## Suitable Application

Power Limited Fire Alarm Signaling Cable  
Monitor/Detection  
Audio Circuits  
Control Circuits

## Standards

NEC Articles: 725, 760, 800  
22-16 AWG: CMP, CL2P, CL3P, FPLP  
14-12 AWG: CL3P, FPLP

## Applicable Standards

UL Type	FPLP, CL2P
ROHS Compliant	Yes

## Electricals

Conductors	ASTM B-3
Temperature Rating	-4°C to 75°C
DC Resistance	2.43 Ohms/1M'
Capacitance	24 pF/ft

## Print Legend

COMMODITY CABLES, INC. 14 AWG 2C PLENUM FIRE ALARM CABLE (UL) TYPE CL2P/ FPLP E498766 A1001.

Toll Free: (866) 945-5051  
Local: (770) 945-5051  
Fax: (770) 945-9582  
[www.commoditycables.com](http://www.commoditycables.com)



## Construction Details

Total Number Conductors	2
AWG	14
Stranding	Solid
Conductor Material	Bare copper
Insulation Material	Low smoke copolymer
Insulation Thickness	.010"
Nominal Insulation Diameter	.084"
Color Code	Black, Red
Cabling Overall Lay	4" left hand lay
Nominal Cabling Diameter	.169"
Final Jacket Material	Low smoke copolymer
Nominal Thickness	.015"
Jacket Color	Red
Nominal Jacket Diameter	.198"
Ripcord	Yes

## Print (Surface Print)

Inkjet	Yes
Sequential Foot Marks	Yes

## Preparation for Shipment

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available. Shipping containers shall be constructed as to eliminate any possible damage to the cables due to shipment.

\*All values in this specification are nominal and are subject to tolerances of +/- 10 to 15%. It is the sole responsibility of the user to have the most current specification. Specifications are subject to change without notice\*