



www.commoditycables.com

PART NO. 1602SCMRRX

### Description

16 AWG 2 Conductor riser rated jacket

### Features and Benefits

RoHS Compliant

Cables are manufactured to meet current NEC guidelines and are verified by outside standards organizations including c(UL)us and c(ETL)us.

Footage marked descending.

### Suitable Application

- Security Systems
- Sound/Audio System
- Intercom Systems
- Power-Limited Controls

### Standards

NEC Articles: 25, 760, 800

22-16 AWG: CMR, CL2R, CL3R, FPLR

14-12 AWG: CL3R, FPLR

### Applicable Standards

UL Type	CL2R, CL3R, FPLR
ROHS Compliant	Yes

### Electricals

Operating Voltage	300 V
Temperature Rating	-4°C to 75°C
Nom Capacitance	34 pF/ft

### Print Legend

COMMODITY CABLES, INC. 16 AWG 2C (UL) TYPE CL3R/FPLR OR c(UL)us TYPE CMR E498766 A1001.

Toll Free: (866) 945-5051

Local: (770) 945-5051

Fax: (770) 945-9582

www.commoditycables.com

### Construction Details

Total Number Conductors	2
AWG	16
Stranding	19 Strand
Conductor Material	Bare copper
Insulation Material	PVC
Insulation Thickness	.009"
Nominal Insulation Diameter	.074"
Color Code	Black/Red
Tape Material	Aluminium Mylar
Cabling Overall Lay	3 1/2" left hand lay
Final Jacket Material	PVC
Nominal Thickness	.015"
Jacket Color	White/Gray
Nominal Jacket Diameter	.188"
Weight	26 lb
Ripcord	Yes

### Print (Surface Print)

Inkjet	Yes
Sequential Foot Marks	Yes

### Preparation for Shipment

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available. Shipping containers shall be constructed as to eliminate any possible damage to the cables due to shipment.



\*All values in this specification are nominal and are subject to tolerances of +/- 10 to 15%. It is the sole responsibility of the user to have the most current specification. Specifications are subject to change without notice\*