


**DESCRIPTION:**
**RG11 CMR COAXIAL 1000 FEET BLACK  
WOODEN REEL**
**Category: RG11 CMR**
**Test Standard: ETL**

**PERFORMANCE**

Frequency (MHz)	ATT (dB)
55	0.96
211	1.90
300	2.25
400	2.60
550	3.05
750	3.65
870	4.00
1000	4.36
1350	4.98
1750	6.00
2150	6.70
2600	7.63
3000	8.24

**STANDARD PACKAGE**

Packing	Wooden Reel
Weight	58 lbs
Packing Length	1000 ft

**CONSTRUCTION DETAILS**

Conductor	Material	Solid copper clad steel				
	Nom. O.D. (mm)	1.63	<table border="1"> <tr> <td>up</td> <td>+0.01</td> </tr> <tr> <td>down</td> <td>-0.01</td> </tr> </table>	up	+0.01	down
up	+0.01					
down	-0.01					
Insulation	Material	Foam PE				
	Diameter	7.11± 0.15 mm				
First Shield	Material	Aluminum/PET-Foil-Bonded				
Second Shield	Material	Aluminum Wire				
	Construction	0.15mm×16×16				
Sheath	Nom. Thickness	1.0mm				
	External O.D	10.00±0.20mm				
	Material	PVC(complies RoHS				
	Color	BLACK				
Sheath Physical Properties	Before Aging Tensile Strength (Mpa)	≥13.8				
	Elongation(%)	≥180				
Electrical Characteristics (20°C)	Nom. Centre Conductor DC Resistance	13.0 ohm/kft				
	Velocity of Propagation (%)	85%				
	Nominal Capacitance	15.6 pF/ft				
	Impedance	75±3 Ohms				
	Jacket Spark Test Voltage	AC 3000V				
Temperature Range	-20°C to +70°C					

Toll Free: (866) 945-5051  
 Local: (770) 945-5051  
 Fax: (770) 945-9582  
[www.commoditycables.com](http://www.commoditycables.com)

