


**RG11 STANDARD TYPE, 60% BRAID COAXIAL CABLE**
**PART NO. 11OUTWCCSRX**
**DESCRIPTION:**

RG11 STANDARD TYPE, 60% BRAID CO-AXIAL CABLE, PE JACKET, FLOODED FOR UNDERGROUND 1000 FT WOOD REEL

Category: RG11 CMR

Test Standard: ETL. UV Resistant


**PERFORMANCE**

Frequency (MHz)	ATT (dB)
55	0.96
211	1.90
300	2.25
400	2.60
550	3.05
750	3.65
870	4.00
1000	4.36

**STANDARD PACKAGE**

Packing	Wooden Reel
Weight	46 lbs
Packing Length	1000 ft

Toll Free: (866) 945-5051  
 Local: (770) 945-5051  
 Fax: (770) 945-9582  
[www.commoditycables.com](http://www.commoditycables.com)

**CONSTRUCTION DETAILS**

Conductor	Material	Solid copper clad steel		
	Nom. O.D. (mm)	1.63	up	+0.01
			down	-0.01
Insulation	Material	Foam PE		
	Diameter	7.11± 0.15 mm		
First Shield	Material	Aluminum/PET-Foil-Bonded		
Second Shield	Material	Aluminum Wire		
	Construction	0.15mm×16×16		
Flooded	Material	Water blocking tape		
Sheath	Nom. Thickness	1.0mm		
	External O.D	10.00±0.20mm		
	Material	PE(complies RoHS)		
	Color	BLACK		
Sheath Physical Properties	Before Aging Tensile Strength (Mpa)	≥15.0		
	Elongation(%)	≥500		
Electrical Characteristics (20°C)	Nom. Centre Conductor DC Resistance	13.0 ohm/kft		
	Velocity of Propagation (%)	85%		
	Nominal Capacitance	15.6 pF/ft		
	Impedance	75±3 Ohms		
	Jacket Spark Test Voltage	AC 3000V		
Temperature Range	-40°C to +80°C			