



PART NO. 1602UCMRRX

www.commoditycables.com

Description

16 AWG 2 Conductor riser rated jacket

Features and Benefits

RoHS Compliant
Cables are manufactured to meet current NEC guidelines and are verified by outside standards organizations
Footage marked descending.

Suitable Application

Security Systems
Sound/Audio System
Intercom Systems
Power-Limited Controls

Standards

NEC Articles: 725, 760, 800
22-16 AWG: CMR, CL2R, CL3R, FPLR
14-12 AWG: CL3R, FPLR

Applicable Standards

Table with 2 columns: Standard Name, Value. Rows: UL Type (CMR, CL3R, FPLR), ROHS Compliant (Yes)

Electricals

Table with 2 columns: Property, Value. Rows: Operating Voltage (300 V), Temperature Rating (-4°C to 75°C), Nom Capacitance (34 pF/ft)

Print Legend

COMMODITY CABLES, INC. 16 AWG 2c TYPE CL3R/FPLR OR TYPE CMR E498766 A1001.

Toll Free: (866) 945-5051
Local: (770) 945-5051
Fax: (770) 945-9582
www.commoditycables.com

Construction Details

Table with 2 columns: Property, Value. Rows: Total Number Conductors (2), AWG (16), Stranding (19 Strand), Conductor Material (Bare copper), Insulation Material (Polyvinylchloride), Insulation Thickness (.009"), Nominal Insulation Diameter (.074"), Color Code (Black/Red), Cabling Overall Lay (3 1/2" left hand lay), Final Jacket Material (Polyvinylchloride), Nominal Thickness (.015"), Jacket Color (White/Gray), Nominal Jacket Diameter (.179"), Ripcord (Yes)

Print (Surface Print)

Table with 2 columns: Property, Value. Rows: Inkjet (Yes), Sequential Foot Marks (Yes)

Preparation for Shipment

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available. Shipping containers shall be constructed as to eliminate any possible damage to the cables due to shipment.



All values in this specification are nominal and are subjective to tolerances of +/- 10 to 15%. It is the sole responsibility of the user to have the most current specification. Specifications are subject to change without notice