



PART NO. 1604UCMPRX

www.commoditycables.com

**Description**

16 AWG 4 Conductor PVC jacket

**Features and Benefits**

RoHS Compliant  
 Cables are manufactured to meet current NEC guidelines and are verified by outside standards organizations  
 Footage marked descending.

**Suitable Application**

Security Systems  
 Sound/Audio System  
 Intercom Systems  
 Power-Limited Controls

**Standards**

NEC Articles: 725, 760, 800  
 22-16 AWG: CMP, CL2P, CL3P, FPLP  
 14-12 AWG: CL3P, FPLP

**Applicable Standards**

UL Type	CMP, CL3P, FPLP
ROHS Compliant	Yes

**Electricals**

Operating Voltage	300 V
Temperature Rating	-4°C to 75°C

**Print Legend**

COMMODITY CABLES, INC. 16 AWG 2C TYPE CL3P/FPLP OR c(UL)us TYPE CMP E498766 A1001.

Toll Free: (866) 945-5051  
 Local: (770) 945-5051  
 Fax: (770) 945-9582  
[www.commoditycables.com](http://www.commoditycables.com)

**Construction Details**

Total Number Conductors	4
AWG	16
Stranding	19 Strand
Conductor Material	Bare copper
Insulation Material	Low smoke PVC
Insulation Thickness	.010"
Nominal Insulation Diameter	.084"
Color Code	Black/Red/White/Green
Cabling Overall Lay	3 1/2" left hand lay
Final Jacket Material	Low smoke PVC
Nominal Thickness	.018"
Jacket Color	White/Gray
Nominal Jacket Diameter	.211"
Ripcord	Yes

**Print (Surface Print)**

Inkjet	Yes
Sequential Foot Marks	Yes

**Preparation for Shipment**

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available. Shipping containers shall be constructed as to eliminate any possible damage to the cables due to shipment.



\*All values in this specification are nominal and are subjective to tolerances of +/- 10 to 15%. It is the sole responsibility of the user to have the most current specification. Specifications are subject to change without notice\*