



www.commoditycables.com

PART NO. 1803UCMRRX

### Description

18 AWG stranded bare copper 3 conductor riser

### Features and Benefits

#### RoHS Compliant

Cables are manufactured to meet current NEC guidelines and are verified by outside standards organizations.

Footage marked descending.

### Suitable Application

- Security Systems
- Sound/Audio System
- Intercom Systems
- Power-Limited Controls

### Standards

- NEC Articles: 725, 760, 800
- 22-16 AWG: CMR, CL2R, CL3R, FPLR
- 14-12 AWG: CL3R, FPLR

### Applicable Standards

UL Type	CMR, CL2R, CL3R, FPLR
ROHS Compliant	Yes

### Electricals

Voltage Rating	300 V
Temperature Rating	-4°C to 75°C
Conductors	ASTM B-8
Capacitance	20.5 pF/ft

### Print Legend

COMMODITY CABLES, INC. 18 AWG 3C TYPE CL3R/FPLR OR TYPE CMR E498766 A1001.

Toll Free: (866) 945-5051  
 Local: (770) 945-5051  
 Fax: (770) 945-9582  
[www.commoditycables.com](http://www.commoditycables.com)

### Construction Details

Total Number Conductors	3
AWG	18
Stranding	7 Strand
Conductor Material	Bare copper
Insulation Material	Polyvinylchloride
Insulation Thickness	.009"
Nominal Insulation Diameter	.064"
Color Code	Black, Red, White
Cabling Overall Lay	3" left hand lay
Final Jacket Material	Polyvinylchloride
Nominal Thickness	.015"
Jacket Color	White/Gray
Nominal Jacket Diameter	.168"
Ripcord	Yes

### Print (Surface Print)

Inkjet	Yes
Sequential Foot Marks	Yes

### Preparation for Shipment

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available. Shipping containers shall be constructed as to eliminate any possible damage to the cables due to shipment.



\*All values in this specification are nominal and are subjective to tolerances of +/- 10 to 15%. It is the sole responsibility of the user to have the most current specification. Specifications are subject to change without notice\*