



www.commoditycables.com

PART NO. 2202UCMPBX

Description

22 AWG two Conductor plenum rated

Features and Benefits

RoHS Compliant
Cables are manufactured to meet current NEC guidelines and are verified by outside standards organizations.
Footage marked descending.

Suitable Application

Security Systems
Sound/Audio System
Intercom Systems
Power-Limited Controls

Standards

NEC Articles: 725, 760, 800
22-16 AWG: CMP, CL2P, CL3P, FPLP
14-12 AWG: CL3P, FPLP

Applicable Standards

Table with 2 columns: Standard Name, Value. Rows: UL Type (CMP, CL3P, FPLP), ROHS Compliant (Yes).

Electricals

Table with 2 columns: Property, Value. Rows: Voltage Rating (300 Volts), Temperature Rating (-4°C to 75°C), Conductors (ASTM B-8), Capacitance CDR (20.5 pF/ft).

Print Legend

COMMODITY CABLES, INC. 22 AWG 2C
TYPE CL3P/FPLP OR TYPE CMP E498766
A1001.

Toll Free: (866) 945-5051
Local: (770) 945-5051
Fax: (770) 945-9582
www.commoditycables.com



Construction Details

Table with 2 columns: Property, Value. Rows: Total Number Conductors (2), AWG (22), Stranding (7 Strand), Conductor Material (Bare copper), Insulation Material (Low smoke copolymer), Insulation Thickness (.007"), Nominal Insulation Diameter (.043"), Color Code (Black, Red), Cabling Overall Lay (2 1/2" left hand lay), Final Jacket Material (Low smoke copolymer), Nominal Thickness (.015"), Jacket Color (White/Gray), Nominal Jacket Diameter (.116"), Ripcord (Yes).

Print (Surface Print)

Table with 2 columns: Property, Value. Rows: Inkjet (Yes), Sequential Foot Marks (Yes).

Preparation for Shipment

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available. Shipping containers shall be constructed as to eliminate any possible damage to the cables due to shipment.

All values in this specification are nominal and are subjective to tolerances of +/- 10 to 15%. It is the sole responsibility of the user to have the most current specification. Specifications are subject to change without notice