

# PART NO. 1803UCMPRX

www.commoditycables.com

### Description

18 AWG stranded bare copper 3 conductor Plenum

#### **Features and Benefits**

RoHS Compliant Cables are manufactured to meet current NEC guidelines and are verified by outside standards organizations. Footage marked descending.

## Suitable Application

Security Systems Sound/Audio System Intercom Systems Power-Limited Controls

#### **Standards**

NEC Articles: 725, 760, 800 22-16 AWG: CMP, CL2P, CL3P, FPLP 14-12 AWG: CL3P, FPLP

#### **Applicable Standards**

UL Type	CMP, CL2P, CL3P, FPLP
ROHS	Yes
Compliant	

#### Electricals

Voltage Rating	300 V
Temperature	-4°C to 75°C
Rating	
Conductors	ASTM B-8
Capacitance	20.5 pF/ft

#### **Print Legend**

COMMODITY CABLES, INC. 18 AWG 3C TYPE CL3P/FPLP OR TYPE CMP E498766 A1001.

Toll Free: (866) 945-5051 Local: (770) 945-5051 Fax: (770) 945-9582 www.commoditycables.com







Construction Details	
Total Number Conductors	3
AWG	18
Stranding	7 Strand
Conductor Material	Bare copper
Insulation Material	Low smoke copolymer
Insulation Thickness	.009"
Nominal Insulation Diameter	.064"
Color Code	Black, Red, White
Cabling Overall Lay	3" left hand lay
Final Jacket Material	Low smoke copolymer
Nominal Thickness	.015"
Jacket Color	White, Gray
Nominal Jacket Diameter	.168"
Ripcord	Yes

Print (Surface Print)	
Inkjet	Yes
Sequential Foot Marks	Yes

## Preparation for Shipment

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available. Shipping containers shall be constructed as to eliminate any possible damage to the cables due to shipment.

\*All values in this specification are nominal and are subjective to tolerances of +/- 10 to 15%.

It is the sole responsibility of the user to have the most current specification. Specifications are subject to change without notice\*