

Control Cable

Stranded No Shield

Product Construction

Conductor:

Annealed Solid or Stranded bare copper

Insulation:

FR-PVC

Color code: see chart below

Jacket:

FR-PVC Gray or White

Suitable for use from -20°C to +75°C

Every 2 feet sequential marking

Include ripcord

Applications:

Power-limited control circuits

Wiring of following systems:

Intercom

Security

Audio

Background music

Compliances:

UL type CL3R

UL type CMR

Sun Resistant

ROHS REACH

Suggested voltage rating:300V

Cable printing:

COMMODITY CABLES CONTROL CABLE UNSHIELD (ETL) CCI# xC/xxAWG xxSTRAND 75C TYPE CL3R CMR ROHS (quality code) 0002---1000FT

PART NO.	NO.of Cond.	AWG Size	om. Insualtion Dia.m	Nom. Jacket Dia. mm	standard lengths
2202UCMRBX	2	22(7/30)	1.02	3.1	1000'
1802UCMRRW/1802UCMRRG	2	18(7/26)	1.42	3.8	1000'
1803UCMRRW/1803UCMRRG	3	18(7/26)	1.42	4.2	1000'
1804UCMRRG	4	18(7/26)	1.42	4.75	1000'
1602UCMRRW/1602UCMRRG	2	16(19/0.0117)	1.8	4.5	1000'
1604UCMRRX	2	16(19/0.0117)	1.8	5.3	1000'
1402UCMRRW	2	14(19/0.0147)	2.3	5.6	1000'

Color Code Chart

No. of Cond.	Color
1	Red
2	Black
3	White
4	Green

