

DESCRIPTION

• 23 AWG 4 Pair S/FTP Category 7 cable
tested to 600 MHz Plenum grade, high performance
for top level network cabling for maximum
headroom and bandwidth. Available in reel
for easier installation.

FEATURES AND BENEFITS

- supports up to 600 MHz maximum frequency and 10 Gbps ten-gigabit transmission, equipped with full shielding to resist electromagnetic interference
- Improved cable temperature rating (75°C Riser) for greater protection against in creased operating temperatures
- Sequential footage markings
- Verified by third-party for guaranteed performance

APPLICATIONS

- . 100Base-T4
- . 100Base-TX
- . 1000Base-T
- . 1000Base-TX
- . 155Mbps ATM
- . 622Mbps ATM
- . 10 Gb Ethernet
- . IEEE 802.3af/at/bt

REFERENCE STANDARD

- ISO/IEC 61156
- ISO/IEC 11801 Ed. 2.0 (Class F)
- UL444
- NFPA262
- REACH Compliant
- RoHS Compliant Directive 2002/95/EG

Toll Free: (866) 945-5051

Local: (770) 945-5051


Fax: (770) 945-9582

www.commoditycables.com



CAT7 S/FTP 23AWG/4PAIR CMP 10GIG

PART NO. 7CMP234RX



PHYSICAL PROPERTIES

Conductor	Material	Solid Bare Copper
	Diameter (±0.01mm)	0.57
	Material	FOAM PE
Insulation	Insulation Dia (±0.05mm)	1.32
	Colour	Blue/White-Blue Orange/White-Orange Green/White-Green Brown/White-Brown
		100% coverage
Shielded	AL-Mylar	0.4TC
	Drain Wire (±0.01mm)	ALMg braid Density≥40%
	Braid	
Rip cord	Yes	
Jacket	Material	PVC PLENUM
	Jacket Diameter (±0.3mm)	7.8
	Thickness (±0.1mm)	0.55
Put/UPs	Length (±4ft)	1000
	Weight	17.4KGS
VoltageRating (Max)		DC 60V
Flame Test Method		NFPA262 CMP

Electrical properties @ 20°C

conductor resistance	≤78Ω/km
Conductor resistance unbalance	≤5%(@20°C)
Delay skew	≤25ns/100m
Working capacity	≤5.6nF/100m(@1kHz)
insulation resistance	≥5000MΩ.km
Capacitive unbalance to earth	≤330 pF/100m(@1kHz)
Impedance	100±25Ω

Mechanical properties

Operating temperature	-20~75°C
Minimum bending radius	4×Cable OD
Jacket Elongation at break	≥100%
Jacket Tensile strength	≥13.8Mpa
Jacket Aging conditions	100 °C 240h
Jacket Elongation at break After Aging	≥50% Before Aging
Jacket Tensile Strength After Aging	≥85% Before Aging
Low temperature winding experiment	-20°C 4h No visible cracks



CAT7 S/FTP 23AWG/4PAIR CMP 10GIG

PART NO. 7CMP234RX

Transmission performance:(@20°C/100m)

Frequency (MHz)	ATT (< dB)	NEXT (> dB)	PSNEXT (> dB)	ACRF (> dB)	PSACRF (> dB)	RL (> dB)	Delay (< ns)	Spread out 100m cable and test it
4.00	3.7	78.0	75.0	78.0	75.0	23.0	552.0	
8.00	5.2	78.0	75.0	75.9	74.2	24.5	547.0	
10.00	5.9	78.0	75.0	74.0	72.3	25.0	545.0	
16.00	7.4	78.0	75.0	69.9	68.2	25.0	543.0	
20.00	8.3	78.0	75.0	68.0	66.3	25.0	542.0	
25.00	9.3	78.0	75.0	66.0	64.3	24.3	541.0	
31.25	10.4	78.0	75.0	64.1	62.4	23.6	540.0	
62.50	14.9	75.5	72.5	58.1	56.4	21.5	539.0	
100.00	19.0	72.4	69.4	54.0	52.3	20.1	538.0	
200.00	27.5	67.9	64.9	48.0	46.3	18.0	537.0	
250.00	31.0	66.4	63.4	46.0	44.3	17.3	536.0	
300.00	34.2	65.2	62.2	44.5	42.8	17.3	536.0	
400.00	40.0	63.4	60.4	42.0	40.3	17.3	536.0	
500.00	45.3	61.9	58.9	40.0	38.3	17.3	536.0	
600.00	50.1	60.7	57.7	38.4	36.7	17.3	535.0	

*Values Table parameters are for reference only

AVAILABLE CATEGORY 7 (PART NUMBERS)

BLUE 7CMP234RO

WHITE 7CMP234RW

Toll Free: (866) 945-5051

Local: (770) 945-5051

Fax: (770) 945-9582

www.commoditycables.com



AVAILABLE JACKET COLORS			
STANDARD	BLUE	WHITE	GRAY
	BLACK	RED	GREEN
	YELLOW	ORANGE	PURPLE
	PINK		
	SPECIAL	Per Customer Request*	
INSULATION COLORS			
PAIR 1	BLUE	WHITE	
PAIR 2	ORANGE	WHITE	
PAIR 3	GREEN	WHITE	
PAIR 4	BROWN	WHITE	

JACKETS ABBREVIATION

Black	B	Last alphabetical character of each part number indicates the color code that the Jacket is available in. For example Part # 6CMR244Bx ("x" indicates all the colors to the left are available for this product.
White	W	
Gray	G	
Blue	O	
Yellow	Y	
Green	V	
Orange	OR	
Purple	P	
Red	R	
Pink	PI	