

Plenum Grade THERMOSTAT CABLE

Product Construction

Conductor:

Annealed Solid bare copper

Insulation:

LS FR-PVC

Color code: see chart below

Jacket:

LS FR-PVC Brown or White

Suitable for use from -20°C to +75°C

Every 2 feet sequential marking

Applications:

Used for power limited circuits such as thermostat, air conditioning and heating controls, heat pumps, bell and alarm systems, intercom systems, door bells, remote control units where maximum voltage does not exceed 30 volts.

Compliances:

UL13 type CL3P

UL13 type CL2P

Sun Resistant

ROHS REACH

NO.of Cond.	AWG Size	Insulation Dia.mm	Jacket thickness mm
-------------	----------	-------------------	---------------------

2	18	1.45	0.4
3	18	1.45	0.4
4	18	1.45	0.4
5	18	1.45	0.4
6	18	1.45	0.4
7	18	1.45	0.4
8	18	1.45	0.4
9	18	1.45	0.4
10	18	1.45	0.4
12	18	1.45	0.4

2	20	1.25	0.4
3	20	1.25	0.4
4	20	1.25	0.4
5	20	1.25	0.4
6	20	1.25	0.4
7	20	1.25	0.4
8	20	1.25	0.4
9	20	1.25	0.4
10	20	1.25	0.4
11	20	1.25	0.4
12	20	1.25	0.4

Color Code Chart

No. of Cond.	Color	No. of Cond.	Color
1	Red	7	Orange
2	White	8	Black
3	Green	9	Pink
4	Blue	10	Gray
5	Yellow	11	Tan
6	Brown	12	Purple

Cable printing:

COMMODITY CABLES THERMOSTAT CABLE (part NO.) xC/xxAWG (ETL) 5013739 CL2P CL3P SUNLIGHT RESISTANT

RoHS 0002---xxxFT