

3. Mobile Home Feeder Cable- 600V

Application: COMMODITY cables Mobile Home Feeder Cable is listed for direct burial applications and approved for use in raceways and underground installations in accordance with the requirements of the National Electrical Code. Suitable for direct burial in earth at conductor temperatures not to exceed 90°C. Voltage rating is 600 volts

Conductors: AA-8000 series aluminum alloy compacted conductors.

Insulation: Cross-linked polyethylene (XLPE) insulation. The insulation is sunlight resistance.

Standards: Type RHH or RHW-2 or USE-2 conductors are UL Standard 44 for RHW-2, UL Standard 854 for USE-2, National Electrical Code, NFPA 70, 2011 Edition and RoHS Compliant, ASTM B 800 & ASTM B 801.



SIZE (AWG)	PHASE CONDUCTOR		NEUTRAL CONDUCTOR		GROUNDING CONDUCTOR		OVERALL CABLE DIA	APPROX WT /	AMP
	Stranding	DIA. (Mils)	Stranding	DIA. (Mils)	Stranding	DIA. (Mils)	DIA.(Mils)	1000 (LBS)	
2-2-4-6	7	388	7	333	7	292	937	301	100
2-2-2-4	7	388	7	388	7	333	937	345	100
2/0-2/0-1-4	19	536	19	459	7	333	1294	555	150
2/0-2/0-2/0-1	19	536	19	536	19	459	1294	673	150
4/0-4/0-2/0-4	19	635	19	536	7	333	1533	784	200
4/0-4/0-4/0-2/0	19	635	19	635	19	536	1533	993	200

1. Data are approximate and subject to normal manufacturing tolerances.
2. Standard lengths are subject to normal manufacturing tolerance of +/- 10%

